

Performance Chart

Model	Ejector Type	Discharge Pressure (psig)	Depth to water (feet)					
			30	40	50	60	70	80
			Capacities U.S. gpm*					
JDF2A	E20	20	12.0	7.0				
		30	4.6					
		35						
		45						
		SHUTOFF (psi)						
	E25	20	10.4	8.5	6.5			
		30	5.8	4.5	2.9			
		35	3.8	2.5	1.1			
		45	1.0					
		SHUTOFF (psi)	0.8	0.7	0.7			
	E30	20	8.3	7.1	6.2	4.1	3.3	
		30	5.9	4.9	4.0	2.6	1.8	
		35	4.8	3.8	2.9	1.6		
		45	2.9	2.0	1.3			
		50	2.0	1.25				
SHUTOFF (psi)	1.0	0.9	0.9					
JDF4A	E20	20	18	9.0	1.6			
		30	8.3	2.7	0.8			
		35	3.4	1.0				
		45						
		SHUTOFF (psi)						
	E25	20	13.3	11.1	8.7			
		30	8.7	6.8	4.8			
		35	6.6	4.6	2.9			
		45	2.6	1.0				
		SHUTOFF (psi)	0.8	0.8	0.7			
	E30	30		6.0	5.4	4.4	3.5	2.2
		35		5.3	4.3	3.3	2.6	1.8
		45		3.1	2.3	1.6	1.2	
		50		2.2	1.5	1.0	0.5	
		SHUTOFF (psi)		1.2	1.0	1.0	0.9	

* Capacities given are for near-sea level installations.